

Standart (Azami) dikey uygulama montaj uzunlukları

Pilkington **Profilit**™ cam sistemi

Pilkington **Profilit**™ paneller kapanmış ve eğim verilmemiştir

Rüzgar yükü kN/m ²	Tek cam (kenar içeride)						
	K 22 L (m)	K 25 L (m)	K 32 L (m)	K 50 L (m)	K 22/60/7 L (m)	K 25/60/7 L (m)	K 32/60/7 L (m)
0.50	2.70	2.50	2.30	1.90	4.20	4.00	3.60
0.60	2.40	2.30	2.00	1.70	3.85	3.60	3.30
0.70	2.30	2.10	1.90	1.60	3.55	3.40	3.00
0.80	2.10	2.00	1.80	1.50	3.35	3.20	2.85
0.90	2.00	1.90	1.70	1.40	3.10	2.95	2.70
1.00	1.90	1.80	1.60	1.30	3.00	2.80	2.55
1.20	1.70	1.60	1.50	1.20	2.70	2.55	2.30
1.40	1.60	1.50	1.35	1.10	2.50	2.40	2.15
1.60	1.50	1.40	1.25	1.00	2.35	2.20	2.00
1.80	1.40	1.30	1.20	0.95	2.20	2.10	1.90
2.00	1.30	1.20	1.10	0.90	2.10	2.00	1.80
3.00	1.00	1.00	0.90	0.75	1.70	1.60	1.45

Rüzgar yükü kN/m ²	Çift cam						
	K 22 L (m)	K 25 L (m)	K 32 L (m)	K 50 L (m)	K 22/60/7 L (m)	K 25/60/7 L (m)	K 32/60/7 L (m)
0.50	3.80	3.60	3.20	2.70	6.00	5.70	5.10
0.60	3.40	3.25	3.00	2.40	5.40	5.15	4.65
0.70	3.20	3.00	2.70	2.25	5.00	4.75	4.30
0.80	3.00	2.80	2.55	2.10	4.70	4.50	4.00
0.90	2.80	2.70	2.40	2.00	4.40	4.20	3.80
1.00	2.65	2.50	2.30	1.90	4.20	4.00	3.60
1.10	2.55	2.40	2.20	1.80	4.05	3.80	3.45
1.20	2.40	2.30	2.00	1.70	3.80	3.60	3.30
1.40	2.25	2.10	1.90	1.60	3.50	3.40	3.00
1.60	2.10	2.00	1.75	1.45	3.30	3.15	2.80
1.80	2.00	1.90	1.65	1.35	3.10	3.00	2.65
2.00	1.85	1.75	1.55	1.30	3.00	2.80	2.55
3.00	1.50	1.40	1.30	1.00	2.40	2.30	2.00